DesignLights Consortium



DLC QPL / Products / Product Details

Model Number

ASD-CAN09S-A200(BK,WH,BR)-(Blank,8EM,15EM,20EM)

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

Product ID: S-QGNYXK

Product Overview 19 fields

CATEGORY
Outdoor Luminaires

GENERAL APPLICATION
High Output

PRIMARY USE
Parking Garage Luminaires

CLASSIFICATION
Premium

TECHNICAL REQUIREMENTS VERSION
6.0

DLC FAMILY CODE
XPCZGP

BRAND
ASD

PARENT
Yes

LISTING STATUS
Listed

DATE QUALIFIED
2026-10-09

REPORTED INPUT WATTAGE
199.3 W

REPORTED LIGHT OUTPUT
28,170 lm

REPORTED CCT
4000 K

REPORTED CRI
81

REPORTED R9
2

REPORTED IES RF
82

REPORTED IES RG
97

REPORTED IES RCS,H1
-12

INPUT POWER TYPE
AC

SPECIFICATION SHEET
S-QGNYXK Specification Sheet Date Updated: 2026-09-14

Version History 1 records

2026-10-09	Listed	6	Premium

V6.0 Controls Options 1 records

Blank	**1**	10V (wired)	Continuous	0	None	Zhaga Book 18	None	None	None	N/A	N/A

V5.1 Control Features 1 fields

INTEGRAL CONTROL CAPABILITY
No

Reported Photometric Performance 10 fields

REPORTED LIGHT OUTPUT
28170 lm

REPORTED EFFICACY (AC)
141.38 lm/W

REPORTED CCT
4000 K

REPORTED CRI (RA)
81

REPORTED R9
2

REPORTED IES RF
82

REPORTED IES RG
97

REPORTED IES RCS,H1
-12

REPORTED DEFAULT LIGHT OUTPUT
30059 lm

REPORTED BUG RATING
B4 U3 G3

Reported Electrical Performance 5 fields

REPORTED INPUT WATTAGE
199.3 W

REPORTED TOTAL HARMONIC DISTORTION
15 %

REPORTED POWER FACTOR
0.9

REPORTED DEFAULT INPUT WATTAGE
200.0 W

VOLTAGE RANGE
120-277 V

Tested Photometric Performance 11 fields

TESTED VOLTAGE FOR MINIMUM EFFICACY
120

TESTED LIGHT OUTPUT
28170 lm

TESTED EFFICACY (AC)
141.38 lm/W

TESTED CCT
3026 K

TESTED CRI (RA)
81

TESTED R9
2

TESTED IES RF
82

TESTED IES RG
97

TESTED IES RCS,H1
-12 %

TESTED DUV
0

TESTED BUG RATING
B4 U3 G3

Tested Electrical Performance 3 fields

TESTED INPUT WATTAGE
199.26 W

TESTED TOTAL HARMONIC DISTORTION
10.8 %

TESTED POWER FACTOR
0.94

LUNA/Turtle Lighting/Amber No Applicable Data

Field Adjustability 30 fields

FIELD ADJUSTABLE LIGHT OUTPUT (FALO)

Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

Light Output	30059 lm	14500 lm	15000 lm	28500 lm	N/A	N/A	N/A	N/A	N/A
Wattage	200 W	100 W	150 W	200 W	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)

Yes

FACT SETTINGS

4000 K	3000 K	4000 K	5000 K	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)

No

Tunability No Applicable Data

Solar No Applicable Data

Sustainability No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number