



Model Number

ASD-WLP01-80A-PC-[BLANK, 15EM]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-PT6ZKZ



Product Overview

19 fields

CATEGORY

Outdoor Luminaires

GENERAL APPLICATION

High Output

PRIMARY USE

Outdoor Uplight-Emitting Wall-Mounted Area Luminaire

CLASSIFICATION

Premium

TECHNICAL REQUIREMENTS VERSION

6.0

DLC FAMILY CODE

[CCCITZ](#)

BRAND

ASD

PARENT

No

LISTING STATUS

Listed

DATE QUALIFIED

2024-05-28

REPORTED INPUT WATTAGE

80.0 W

REPORTED LIGHT OUTPUT

11,579 lm

REPORTED CCT

3000 K

REPORTED CRI

82

REPORTED R9

3

REPORTED IES RF

84

REPORTED IES RG

96

REPORTED IES RCS,H1

-12

INPUT POWER TYPE

AC

Version History 2 records

2026-06-16	Listed	6	Premium
2025-06-23	Listed	5.1	Premium

V6.0 Controls Options 1 records

PC	3B	10V (wired)	Continuous	10	None	None	None	Photocell only	Light-dependent Resistor	N/A	N/A
----	----	----------------	------------	----	------	------	------	----------------	--------------------------	-----	-----

V5.1 Control Features 6 fields

INTEGRAL CONTROLS

Yes

DIMMING CAPABILITY AND RANGE

Continuous Dimming to 10% or below

INTEGRAL CONTROL CAPABILITY

No

SENSOR TYPE

Exterior Photocell, Multifunction Sensor, Occupancy Sensing

SSL V5 WIRED COMMUNICATION PROTOCOL

0-10V Analog

SSL V5 WIRELESS COMMUNICATION PROTOCOL

No

Reported Photometric Performance 10 fields**REPORTED LIGHT OUTPUT**

11579 lm

REPORTED EFFICACY (AC)

144.72 lm/W

REPORTED CCT

3000 K

REPORTED CRI (RA)

82

REPORTED R9

3

REPORTED IES RF

84

REPORTED IES RG

96

REPORTED IES RCS,H1

-12

REPORTED DEFAULT LIGHT OUTPUT

11579 lm

REPORTED BUG RATING

B2 U5 G5

Reported Electrical Performance 5 fields

REPORTED INPUT WATTAGE

80.0 W

REPORTED TOTAL HARMONIC DISTORTION

15 %

REPORTED POWER FACTOR

0.9

REPORTED DEFAULT INPUT WATTAGE

80.0 W

VOLTAGE RANGE

120-277 V

Tested Photometric Performance No Applicable Data**Tested Electrical Performance** No Applicable Data**LUNA/Turtle Lighting/Amber** No Applicable Data**Field Adjustability** 28 fields**FIELD ADJUSTABLE LIGHT OUTPUT (FALO)**

Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

Light Output	7236 lm	8683.2 lm	11579 lm	N/A	N/A	N/A	N/A	N/A
Wattage	50 W	60 W	80 W	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)

Yes

FACT SETTINGS

3000 K	3000 K	4000 K	5000 K	N/A	N/A	N/A	N/A	N/A
--------	--------	--------	--------	-----	-----	-----	-----	-----

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)

No

Tunability No Applicable Data

Solar No Applicable Data

Sustainability No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number