

# DesignLights Consortium



DLC QPL / Products / Product Details

Model Number

**ASD-UHB2A-NEOX-300[BK;WH;BR;SL]**

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-392RK4



## Product Overview 19 fields

**CATEGORY**

Indoor Luminaires

**GENERAL APPLICATION**

High-Bay

**PRIMARY USE**

High-Bay Luminaires for Commercial and Industrial Buildings

**CLASSIFICATION**

Premium

**TECHNICAL REQUIREMENTS VERSION**

6.0

**DLC FAMILY CODE**

[WWWYIJ](#)

**BRAND**

ASD

**PARENT**

No

**LISTING STATUS**

Listed

**DATE QUALIFIED**

2025-07-10

**REPORTED INPUT WATTAGE**

303.2 W

**REPORTED LIGHT OUTPUT**

53,758 lm

**REPORTED CCT**

3000 K

**REPORTED CRI**

72

**REPORTED R9**

-38

**REPORTED IES RF**

76

**REPORTED IES RG**

92

**REPORTED IES RCS,H1**

-17

**INPUT POWER TYPE**

AC

**SPECIFICATION SHEET**

[S-392RK4 Specification Sheet](#) Date Updated: 2026-07-09

**Version History** 2 records

|            |        |     |         |
|------------|--------|-----|---------|
| 2026-07-10 | Listed | 6   | Premium |
| 2025-07-10 | Listed | 5.1 | Premium |

## V6.0 Controls Options 1 records

|       |   |                |                |   |      |                  |      |      |      |     |     |
|-------|---|----------------|----------------|---|------|------------------|------|------|------|-----|-----|
| Blank | 1 | 10V<br>(wired) | Continuo<br>us | 0 | None | Zhaga<br>Book 18 | None | None | None | N/A | N/A |
|-------|---|----------------|----------------|---|------|------------------|------|------|------|-----|-----|

## V5.1 Control Features 6 fields

### INTEGRAL CONTROLS

No

### DIMMING CAPABILITY AND RANGE

Continuous Dimming to 10% or below

### INTEGRAL CONTROL CAPABILITY

No

### SENSOR TYPE

No

### SSL V5 WIRED COMMUNICATION PROTOCOL

0-10V Analog

### SSL V5 WIRELESS COMMUNICATION PROTOCOL

No

## Reported Photometric Performance 13 fields

### REPORTED LIGHT OUTPUT

53758 lm

### REPORTED EFFICACY (AC)

177.3 lm/W

### REPORTED CCT

3000 K

### REPORTED CRI (RA)

72

### REPORTED R9

-38

### REPORTED IES RF

76

**REPORTED IES RG**

92

**REPORTED IES RCS,H1**

-17

**REPORTED MINIMUM LIGHT OUTPUT**

35460 lm

**REPORTED MAXIMUM LIGHT OUTPUT**

53758 lm

**REPORTED MINIMUM CCT**

3000 K

**REPORTED MAXIMUM CCT**

5000 K

**REPORTED DEFAULT LIGHT OUTPUT**

53758 lm

**Reported Electrical Performance** 7 fields**REPORTED INPUT WATTAGE**

303.2 W

**REPORTED TOTAL HARMONIC DISTORTION**

10.3 %

**REPORTED POWER FACTOR**

0.939

**REPORTED MINIMUM INPUT WATTAGE**

200 W

**REPORTED MAXIMUM INPUT WATTAGE**

303.2

**REPORTED DEFAULT INPUT WATTAGE**

303.2 W

**VOLTAGE RANGE**

120-277 V

**Tested Photometric Performance** No Applicable Data**Tested Electrical Performance** No Applicable Data**Indoor Amber** No Applicable Data**Field Adjustability** 28 fields

FIELD ADJUSTABLE LIGHT OUTPUT (FALO)

Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

|              |          |          |          |     |     |     |     |     |
|--------------|----------|----------|----------|-----|-----|-----|-----|-----|
| Light Output | 35460 lm | 42552 lm | 53758 lm | N/A | N/A | N/A | N/A | N/A |
| Wattage      | 200 W    | 240 W    | 303.2 W  | N/A | N/A | N/A | N/A | N/A |

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)

Yes

FACT SETTINGS

|        |        |        |        |     |     |     |     |     |
|--------|--------|--------|--------|-----|-----|-----|-----|-----|
| 3000 K | 3000 K | 4000 K | 5000 K | N/A | N/A | N/A | N/A | N/A |
|--------|--------|--------|--------|-----|-----|-----|-----|-----|

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)

No

**Tunability** No Applicable Data

**Solar** No Applicable Data

**Sustainability** No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number