

DesignLights Consortium



DLC QPL / Products / Product Details

Model Number

ASD-SWP-MV-A28[BR,BK]-[PC,PC-5EM,blank]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-N7H9HL



Product Overview 19 fields

CATEGORY

Outdoor Luminaires

GENERAL APPLICATION

Low Output

PRIMARY USE

Outdoor Uplight-Emitting Wall-Mounted Area Luminaire

CLASSIFICATION

Premium

TECHNICAL REQUIREMENTS VERSION

6.0

DLC FAMILY CODE

[BCBAHK](#)

BRAND

ASD

PARENT

No

LISTING STATUS

Listed

DATE QUALIFIED

2024-07-11

REPORTED INPUT WATTAGE

27.0 W

REPORTED LIGHT OUTPUT

3,606 lm

REPORTED CCT

3000 K

REPORTED CRI

82

REPORTED R9

8

REPORTED IES RF

83

REPORTED IES RG

99

REPORTED IES RCS,H1

-11

INPUT POWER TYPE

AC

SPECIFICATION SHEET

[S-N7H9HL Specification Sheet](#) Date Updated: 2026-06-29

Version History 2 records

2026-07-10	Listed	6	Premium
2024-07-11	Listed	5.1	Premium

V6.0 Controls Options 2 records

PC	3B	10V (wired)	Continuous	10	None	None	None	Photocell only	Light-dependent Resistor	N/A	N/A
[blank]	1	10V (wired)	Continuous	10	None	Other	None	None	None	N/A	N/A

V5.1 Control Features 6 fields

INTEGRAL CONTROLS

Yes

DIMMING CAPABILITY AND RANGE

Continuous Dimming to 10% or below

INTEGRAL CONTROL CAPABILITY

No

SENSOR TYPE

Exterior Photocell

SSL V5 WIRED COMMUNICATION PROTOCOL

0-10V Analog

SSL V5 WIRELESS COMMUNICATION PROTOCOL

No

Reported Photometric Performance 14 fields

REPORTED LIGHT OUTPUT

3606 lm

REPORTED EFFICACY (AC)

133.51 lm/W

REPORTED CCT

3000 K

REPORTED CRI (RA)

82

REPORTED R9

8

REPORTED IES RF

83

REPORTED IES RG

99

REPORTED IES RCS,H1

-11

REPORTED MINIMUM LIGHT OUTPUT

2670 lm

REPORTED MAXIMUM LIGHT OUTPUT

3606 lm

REPORTED MINIMUM CCT

3000 K

REPORTED MAXIMUM CCT

5000 K

REPORTED DEFAULT LIGHT OUTPUT

3606 lm

REPORTED BUG RATING

B1 U3 G3

Reported Electrical Performance 7 fields**REPORTED INPUT WATTAGE**

27.0 W

REPORTED TOTAL HARMONIC DISTORTION

15 %

REPORTED POWER FACTOR

0.9

REPORTED MINIMUM INPUT WATTAGE

20 W

REPORTED MAXIMUM INPUT WATTAGE

27

REPORTED DEFAULT INPUT WATTAGE

27.0 W

VOLTAGE RANGE

120-277 V

Tested Photometric Performance No Applicable Data**Tested Electrical Performance** No Applicable Data

LUNA/Turtle Lighting/Amber No Applicable Data

Field Adjustability 28 fields

FIELD ADJUSTABLE LIGHT OUTPUT (FALO)
Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

Light Output	2670.2 lm	3204.24 lm	3606 lm	N/A	N/A	N/A	N/A	N/A
Wattage	20 W	24 W	27 W	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)
Yes

FACT SETTINGS

3000 K	3000 K	4000 K	5000 K	N/A	N/A	N/A	N/A	N/A
--------	--------	--------	--------	-----	-----	-----	-----	-----

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)
No

Tunability No Applicable Data

Solar No Applicable Data

Sustainability No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number