# DesignLights Consortium



DLC QPL / Products / Product Details

Model Number

## ASD-LSF8-8A80[WH,BK]-[BLANK,15EM,QB,MS,QB-15EM,MS-15EM]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Standard

Product ID: S-KBVC5K

## Product Overview 19 fields

**CATEGORY**
Indoor Luminaires

**GENERAL APPLICATION**
Linear Ambient

**PRIMARY USE**
Direct Linear Ambient Luminaires

**CLASSIFICATION**
Premium

**TECHNICAL REQUIREMENTS VERSION**
6.0

**DLC FAMILY CODE**
LLLCPV

**BRAND**
ASD

---

**PARENT**
No

**LISTING STATUS**
Listed

**DATE QUALIFIED**
2024-12-16

---

**REPORTED INPUT WATTAGE**
78.9 W

**REPORTED LIGHT OUTPUT**
11,046 lm

**REPORTED CCT**
3500 K

**REPORTED CRI**
83

**REPORTED R9**
10

**REPORTED IES RF**
84

**REPORTED IES RG**
95

**REPORTED IES RCS,H1**
-12

**INPUT POWER TYPE**
AC

---

**SPECIFICATION SHEET**
S-KBVC5K Specification Sheet Date Updated: 2026-07-15

## Version History 2 records

| | | | |
|---|---|---|---|
| 2026-07-23 | Listed | 6 | Premium |
| 2024-12-16 | Listed | 5.1 | Standard |

## V6.0 Controls Options 3 records

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| **QB** | **1** | 10V (wired) | Continuous | 10 | None | Other | None | None | None | N/A | N/A |
| **[blank]** | **1** | 10V (wired) | Continuous | 10 | None | Other | None | None | None | N/A | N/A |
| **MS** | **3A** | 10V (wired) | Continuous | 10 | Dip Switches or Dials | None | None | Occupancy only | Other | 25 | N/A |

## V5.1 Control Features 6 fields

**INTEGRAL CONTROLS**
No

**DIMMING CAPABILITY AND RANGE**
Continuous Dimming to 10% or below

**INTEGRAL CONTROL CAPABILITY**
No

**SENSOR TYPE**
No

**SSL V5 WIRED COMMUNICATION PROTOCOL**
0-10V Analog

**SSL V5 WIRELESS COMMUNICATION PROTOCOL**
No

## Reported Photometric Performance 9 fields

**REPORTED LIGHT OUTPUT**
11046 lm

**REPORTED EFFICACY (AC)**
140 lm/W

**REPORTED CCT**
3500 K

**REPORTED CRI (RA)**
83

**REPORTED R9**
10

**REPORTED IES RF**
84

**REPORTED IES RG**
95

**REPORTED IES RCS,H1**
-12

**REPORTED DEFAULT LIGHT OUTPUT**
11046 lm

## Reported Electrical Performance 5 fields

**REPORTED INPUT WATTAGE**
78.9 W

**REPORTED TOTAL HARMONIC DISTORTION**
15 %

**REPORTED POWER FACTOR**
0.9

**REPORTED DEFAULT INPUT WATTAGE**
79.0 W

**VOLTAGE RANGE**
120-277 V

## Tested Photometric Performance No Applicable Data

## Tested Electrical Performance No Applicable Data

## Indoor Amber No Applicable Data

## Field Adjustability 28 fields

**FIELD ADJUSTABLE LIGHT OUTPUT (FALO)**
Yes

**FALO LIGHT OUTPUT AND WATTAGE SETTINGS**

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **Light Output** | 7700 lm | 10500 lm | 11046 lm | N/A | N/A | N/A | N/A | N/A |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **Wattage** | 55 W | 75 W | 78.9 W | N/A | N/A | N/A | N/A | N/A |

**FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)**

Yes

**FACT SETTINGS**

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 3500 K | 3500 K | 4000 K | 5000 K | N/A | N/A | N/A | N/A | N/A |

**FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)**

No

## Tunability

No Applicable Data

## Solar

No Applicable Data

## Sustainability

No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number