



Model Number

ASD-WLP01-50A-PC-[BLANK, 8EM]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-DSYPB3



Product Overview

19 fields

CATEGORY

Outdoor Luminaires

GENERAL APPLICATION

Mid Output

PRIMARY USE

Outdoor Uplight-Emitting Wall-Mounted Area Luminaire

CLASSIFICATION

Premium

TECHNICAL REQUIREMENTS VERSION

6.0

DLC FAMILY CODE

[CCCITZ](#)

BRAND

ASD

PARENT

Yes

LISTING STATUS

Listed

DATE QUALIFIED

2024-05-28

REPORTED INPUT WATTAGE

50.8 W

REPORTED LIGHT OUTPUT

7,462 lm

REPORTED CCT

3000 K

REPORTED CRI

82

REPORTED R9

3

REPORTED IES RF

84

REPORTED IES RG

96

REPORTED IES RCS,H1

-12

INPUT POWER TYPE

AC

Version History 2 records

2026-06-16	Listed	6	Premium
2025-06-23	Listed	5.1	Premium

V6.0 Controls Options 1 records

PC	3B	10V (wired)	Continuo us	10	None	None	None	Photocel l only	Light- depende nt Resistor	N/A	N/A
----	----	----------------	----------------	----	------	------	------	--------------------	-------------------------------------	-----	-----

V5.1 Control Features 6 fields

INTEGRAL CONTROLS

Yes

DIMMING CAPABILITY AND RANGE

Continuous Dimming to 10% or below

INTEGRAL CONTROL CAPABILITY

No

SENSOR TYPE

Exterior Photocell, Multifunction Sensor, Occupancy Sensing

SSL V5 WIRED COMMUNICATION PROTOCOL

0-10V Analog

SSL V5 WIRELESS COMMUNICATION PROTOCOL

No

Reported Photometric Performance 10 fields**REPORTED LIGHT OUTPUT**

7462 lm

REPORTED EFFICACY (AC)

146.85 lm/W

REPORTED CCT

3000 K

REPORTED CRI (RA)

82

REPORTED R9

3

REPORTED IES RF

84

REPORTED IES RG

96

REPORTED IES RCS,H1

-12

REPORTED DEFAULT LIGHT OUTPUT

7462 lm

REPORTED BUG RATING

B1 U4 G4

Reported Electrical Performance 5 fields

REPORTED INPUT WATTAGE

50.8 W

REPORTED TOTAL HARMONIC DISTORTION

15 %

REPORTED POWER FACTOR

0.9

REPORTED DEFAULT INPUT WATTAGE

51.0 W

VOLTAGE RANGE

120-277 V

Tested Photometric Performance 10 fields**TESTED VOLTAGE FOR MINIMUM EFFICACY**

277

TESTED LIGHT OUTPUT

7385 lm

TESTED EFFICACY (AC)

148.79 lm/W

TESTED CCT

3060 K

TESTED CRI (RA)

82

TESTED R9

3

TESTED IES RF

84

TESTED IES RG

96

TESTED IES RCS,H1

-12 %

TESTED DUV

-0.0002

Tested Electrical Performance 3 fields**TESTED INPUT WATTAGE**

49.63 W

TESTED TOTAL HARMONIC DISTORTION

4.9 %

TESTED POWER FACTOR
0.967

LUNA/Turtle Lighting/Amber No Applicable Data

Field Adjustability 28 fields

FIELD ADJUSTABLE LIGHT OUTPUT (FALO)
Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

Light Output	4405.5 lm	5874 lm	7462 lm	N/A	N/A	N/A	N/A	N/A
Wattage	30 W	40 W	50.81 W	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)
Yes

FACT SETTINGS

3000 K	3000 K	4000 K	5000 K	N/A	N/A	N/A	N/A	N/A
--------	--------	--------	--------	-----	-----	-----	-----	-----

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)
No

Tunability No Applicable Data

Solar No Applicable Data

Sustainability No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number