# DesignLights Consortium



Model Number

## ASD-WLP01-80A-PC-[BLANK, 15EM]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-PT6ZKZ

## Product Overview 19 fields

**CATEGORY**
Outdoor Luminaires

**GENERAL APPLICATION**
High Output

**PRIMARY USE**
Outdoor Uplight-Emitting Wall-Mounted Area Luminaire

**CLASSIFICATION**
Premium

**TECHNICAL REQUIREMENTS VERSION**
6.0

**DLC FAMILY CODE**
CCCITZ

**BRAND**
ASD

---

**PARENT**
No

**LISTING STATUS**
Listed

**DATE QUALIFIED**
2024-05-28

**REPORTED INPUT WATTAGE**
80.0 W

**REPORTED LIGHT OUTPUT**
11,579 lm

**REPORTED CCT**
3000 K

**REPORTED CRI**
82

**REPORTED R9**
3

**REPORTED IES RF**
84

**REPORTED IES RG**
96

**REPORTED IES RCS,H1**
-12

**INPUT POWER TYPE**
AC

## Version History 2 records

| | | | |
|---|---|---|---|
| 2026-06-16 | Listed | 6 | Premium |
| 2025-06-23 | Listed | 5.1 | Premium |

## V6.0 Controls Options 1 records

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| **PC** | **3B** | 10V (wired) | Continuous | 10 | None | None | None | Photocell only | Light-dependent Resistor | N/A | N/A |

## V5.1 Control Features 6 fields

**INTEGRAL CONTROLS**
Yes

**DIMMING CAPABILITY AND RANGE**
Continuous Dimming to 10% or below

**INTEGRAL CONTROL CAPABILITY**
No

**SENSOR TYPE**
Exterior Photocell, Multifunction Sensor, Occupancy Sensing

**SSL V5 WIRED COMMUNICATION PROTOCOL**
0-10V Analog

**SSL V5 WIRELESS COMMUNICATION PROTOCOL**
No

## Reported Photometric Performance 10 fields

**REPORTED LIGHT OUTPUT**
11579 lm

**REPORTED EFFICACY (AC)**
144.72 lm/W

**REPORTED CCT**
3000 K

**REPORTED CRI (RA)**
82

**REPORTED R9**
3

**REPORTED IES RF**
84

**REPORTED IES RG**
96

**REPORTED IES RCS,H1**
-12

**REPORTED DEFAULT LIGHT OUTPUT**
11579 lm

**REPORTED BUG RATING**
B2 U5 G5

## Reported Electrical Performance 5 fields

**REPORTED INPUT WATTAGE**
80.0 W

**REPORTED TOTAL HARMONIC DISTORTION**
15 %

**REPORTED POWER FACTOR**
0.9

**REPORTED DEFAULT INPUT WATTAGE**
80.0 W

**VOLTAGE RANGE**
120-277 V

## Tested Photometric Performance No Applicable Data

## Tested Electrical Performance No Applicable Data

## LUNA/Turtle Lighting/Amber No Applicable Data

## Field Adjustability 28 fields

**FIELD ADJUSTABLE LIGHT OUTPUT (FALO)**
Yes

**FALO LIGHT OUTPUT AND WATTAGE SETTINGS**

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **Light Output** | 7236 lm | 8683.2 lm | 11579 lm | N/A | N/A | N/A | N/A | N/A |
| **Wattage** | 50 W | 60 W | 80 W | N/A | N/A | N/A | N/A | N/A |

**FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)**
Yes

**FACT SETTINGS**

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 3000 K | 3000 K | 4000 K | 5000 K | N/A | N/A | N/A | N/A | N/A |

**FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)**
No

## Tunability No Applicable Data

## Solar No Applicable Data

## Sustainability No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number