



VANITY LIGHT

VF44 series

DESIGN: VANITY LIGHT have a sleek, classic design that will help transform any space in your home. The height selectable cord allows you to customize the fixture and give it the desired look. Durable housing resistant to rust and impact provides many years of service. The opal glass shades grant you even light distribution. It is designed to operate on 120V circuits.

BULBS: The fixture includes a standard E26 medium base which is compatible with a variety of incandescent, CFL or LED bulbs less than 60W.


APPLICATION: These fixtures create a bright light. They are is perfect for bathroom spaces or any other common areas. You can hang these pendants one by one or in a group to create a specific style. They are also Damp Locations rated.

ADVANTAGES: ASD provides a 5-year limited warranty along with ETL certification to guarantee top quality products and safety!




Nickel


FINISH



VF44-2I



VF44-3I



VF44-4I

PRODUCT PRESENTATION

MODEL	BULB TYPE	VOLTAGE	FINISH	DIMENSIONS	CERTIFICATION
ASD-VF44-2I-2660-NK	2 x E26 60W max	120V	Nickel	12 5/8" x 6 3/8" x 7 13/16"	ETL(4001256)
ASD-VF44-3I-2660-NK	3 x E26 60W max	120V	Nickel	20 1/2" x 6 5/16" x 7 13/16"	ETL(4001256)
ASD-VF44-4I-2660-NK	4 x E26 60W max	120V	Nickel	28 3/8" x 6 3/8" x 7 13/16"	ETL(4001256)

TECHNICAL PARAMETERS

MODEL	WORK ENVIRONMENT	OPERATING TEMPERATURE	HOUSING	SHADE
ASD-VF44-2I-2660-NK	Damp location	-4°F to 113°F(-20°C to 45°C)	Steel	Opal glass
ASD-VF44-3I-2660-NK	Damp location	-4°F to 113°F(-20°C to 45°C)	Steel	Opal glass
ASD-VF44-4I-2660-NK	Damp location	-4°F to 113°F(-20°C to 45°C)	Steel	Opal glass

ORDERING INFORMATION

MODEL	PRODUCT DIMENSIONS	WEIGHT	PCS. PER CARTON	CARTON SIZE	CARTON WEIGHT	UPC	GTIN 14
ASD-VF44-2I-2660-NK	12 5/8" x 6 3/8" x 7 13/16"	2.8 lbs(1.3kg)	6	19.69" x 14.96" x 22.64"	25.4 lbs	81005073265	20810050732653
ASD-VF44-3I-2660-NK	20 1/2" x 6 5/16" x 7 13/16"	4.2 lbs(1.9kg)	4	22.83" x 22.83" x 13.78"	22.5 lbs	81005073266	20810050732660
ASD-VF44-4I-2660-NK	28 3/8" x 6 3/8" x 7 13/16"	5.8 lbs(2.6kg)	4	30.31" x 22.83" x 13.78"	32.0 lbs	81005073267	20810050732677

For most up-to-date spec sheets please refer to asd-lighting.com

ASD LIGHTING CORP | www.asd-lighting.com | orders@asd-lighting.com



INSTALLATION GUIDE

Please read all the instructions below before installation!

IMPORTANT SAFETY INFORMATION


- Make sure that the supply voltage corresponds to the rated product voltage.
- The product must be installed by a qualified electrician in accordance with the National Electrical Code and corresponding local codes.
- If the product is damaged, do not use it.

⚠ WARNING

- Risk of personal injury:** read and follow all warnings and installation instructions. Keep or give to the owner for future reference.
- Risk of cuts:** Wear gloves to prevent cuts or abrasions when removing from carton, handling, installing, and maintaining this product.
- Risk of electric shock:** This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
- Risk of Fire:** Minimum 194°F supply conductors. Consult a qualified electrician to ensure correct branch circuit conductor.
- ASD® assumes no responsibility for claims arising out of improper or careless installation or handling of this product.**

PACKAGE CONTENTS

DESCRIPTION	QUANTITY
Vanity Light	1
Mounting bracket (A)	1
Decorative capnut (B)	2
Wire nut (C)	3
Mounting screw (D)	2
Box	1



INSTALLATION STEPS

- Remove the metal ring from the E26 socket, attach the Glass Shade, insert a bulb and secure it with the metal ring.
- Attach the mounting bracket to the outlet box using two mounting screws. Connect the wires: Black to Black, White to White, Ground to Ground. Secure the connection with wire nuts. Carefully tuck all wires back in to the outlet box.
- Place the fixture to the outlet box by aligning two holes on the ceiling plate to the mounting bracket. Tighten the ceiling plate to the mounting bracket using two fixture screws. Installation complete.

