DesignLights Consortium



DLC QPL / Products / Product Details

Model Number

ASD-WLP01-50D50-PC-(EM,Blank)

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-2TN0FX

Product Overview 19 fields

CATEGORY

Outdoor Luminaires

GENERAL APPLICATION

Mid Output

PRIMARY USE

Outdoor Uplight-Emitting Wall-Mounted Area Luminaire

CLASSIFICATION
Premium

TECHNICAL REQUIREMENTS VERSION
6.0

DLC FAMILY CODE
VVWAPJ

BRAND
ASD

PARENT
Yes

LISTING STATUS
Listed

DATE QUALIFIED
2024-05-16

REPORTED INPUT WATTAGE
50.0 W

REPORTED LIGHT OUTPUT
7,707 lm

REPORTED CCT
5000 K

REPORTED CRI
80

REPORTED R9
-8

REPORTED IES RF
81

REPORTED IES RG
95

REPORTED IES RCS,H1
-14

INPUT POWER TYPE
AC

SPECIFICATION SHEET
S-2TN0FX Specification Sheet Date Updated: 2026-06-29

Version History 2 records

2026-07-10	Listed	6	Premium
2024-05-16	Listed	5.1	Premium

V6.0 Controls Options 1 records

PC	**3B**	10V (wired)	Continuous	10	None	None	None	Photocell only	Light-dependent Resistor	N/A	N/A

V5.1 Control Features 6 fields

INTEGRAL CONTROLS
Yes

DIMMING CAPABILITY AND RANGE
Continuous Dimming to 10% or below

INTEGRAL CONTROL CAPABILITY
No

SENSOR TYPE
Exterior Photocell, Occupancy Sensing

SSL V5 WIRED COMMUNICATION PROTOCOL
0-10V Analog

SSL V5 WIRELESS COMMUNICATION PROTOCOL
No

Reported Photometric Performance 10 fields

REPORTED LIGHT OUTPUT
7707 lm

REPORTED EFFICACY (AC)
154.21 lm/W

REPORTED CCT
5000 K

REPORTED CRI (RA)
80

REPORTED R9
-8

REPORTED IES RF
81

REPORTED IES RG
95

REPORTED IES RCS,H1
-14

REPORTED DEFAULT LIGHT OUTPUT
7707 lm

REPORTED BUG RATING
B1 U4 G4

Reported Electrical Performance 5 fields

REPORTED INPUT WATTAGE
50.0 W

REPORTED TOTAL HARMONIC DISTORTION
15 %

REPORTED POWER FACTOR
0.9

REPORTED DEFAULT INPUT WATTAGE
50.0 W

VOLTAGE RANGE
120-277 V

Tested Photometric Performance 10 fields

TESTED VOLTAGE FOR MINIMUM EFFICACY
120

TESTED LIGHT OUTPUT
7707 lm

TESTED EFFICACY (AC)
154.21 lm/W

TESTED CCT
5021 K

TESTED CRI (RA)
80

TESTED R9
-8

TESTED IES RF
81

TESTED IES RG
95

TESTED IES RCS,H1
-14 %

TESTED DUV
0.0024

Tested Electrical Performance 3 fields

TESTED INPUT WATTAGE
50 W

TESTED TOTAL HARMONIC DISTORTION
4.9 %

TESTED POWER FACTOR
0.967

LUNA/Turtle Lighting/Amber No Applicable Data

Field Adjustability No Applicable Data

Tunability No Applicable Data

Solar No Applicable Data

Sustainability No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number