



LED STRIPLIGHT & STAIRWELL FIXTURES

*The best solution
for commercial lighting*



PRODUCT PRESENTATION | 2022

WWW.ASD-LIGHTING.COM



LED STRIPLIGHT & STAIRWELL FIXTURES



LSF5
page 6



LSF5 with MOTION SENSOR
page 7



LSF5 with BATTERY BACK-UP
page 8



LSF5 with MOTION SENSOR & BATTERY BACK-UP
page 9



*The best solution
for commercial lighting*

LED STRIPLIGHT & STAIRWELL FIXTURES

APPLICATION

This fixture is perfect solution for commercial applications such as: offices, schools, hospitals, hallways, stairwells, and more. The fixture is Damp location rated.

ENERGY SAVINGS & EFFICIENCY

This fixture will save you a significant amount of money in its lifetime by providing high lumen output while low energy consumption.

CERTIFICATION & WARRANTY

ASD provides 5-year warranty along with UL and DLC Premium Stairwell and Passageway Luminaires certifications to guarantee top quality products and safety, also allowing participation in rebates.

LED STRIPLIGHT & STAIRWELL FIXTURES

These fixtures have a narrow low-profile design, a smooth PMMA lens for even illumination with no glare, and energy-efficient LED drivers to ensure high performance.

BUILT-IN MOTION SENSOR MODELS

Models with a built-in bi-level microwave Motion Sensor will turn off automatically, when no motion is detected. The sensor can be adjusted using the remote (sold separately).

BUILT-IN BATTERY BACK UP MODELS

Models with a built-in Battery Back-up ensure 90 minutes of power in case of emergency. The indicator light on the side of the fixture allows you to see whether it is in back-up mode or AC mode.

BUILT-IN MOTION SENSOR & BATTERY BACK-UP MODELS

Models with a built-in bi-level microwave Motion Sensor and Battery Back-up are equipped with all optional functions, making them an advanced solution for any commercial application.



MOTION SENSOR

Bi-level adjustable microwave motion sensor

BATTERY BACK-UP

Ensures 90 minutes of power in back-up mode

HOUSING

Durable galvanized metal construction

SAFETY CABLE

Holds optical part during installation

END-CAP

Knock outs on both ends for wiring linked fixtures

POWER AND CCT SWITCHES

Adjust power and color temperature with a simple switch.

DRIVER

Energy-efficient 0-10V dimmable driver provides stable light output, with economic power consumption

LEDs

Highly efficient LEDs provide an output of over 140 lumen per watt

LENS

Smooth PMMA lens with even illumination with no glare

LED STRIPLIGHT FIXTURES

LSF5

LED STRIPLIGHT FIXTURES have a narrow low-profile design, a smooth PMMA lens for even illumination with no glare, and energy-efficient LED drivers to ensure high performance.

Easy to connect multiple fixtures in line using connector (not included).



NARROW, LOW-PROFILE
DESIGN 2 1/2" WIDTH



EASY TO CONNECT FIXTURES
USING CONNECTOR



SUSPENDED OR SURFACE
MOUNTING



**PRODUCT
SIZES**

4 ft, 8 ft



**AVAILABLE
POWER**


22-28-36-44W
48-68-90W



**COLOR
TEMPERATURE**

3 500K, 4 000K, 5 000K

luminous intensity distribution diagram



POWER
ADJUSTABLE



COLOR
ADJUSTABLE



120-277V
voltage



Damp
location

LED STRIPLIGHT & STAIRWELL FIXTURES

LSF5 with Motion Sensor

Models with a built-in bi-level microwave Motion Sensor will turn off automatically, when no motion is detected. The sensor can be adjusted using the remote (sold separately).



AUTOMATIC SWITCH ON/OFF



ADJUSTABLE SENSOR



REMOTE CONTROL
Sold separately



PRODUCT SIZES

4 ft



AVAILABLE POWER

22-28-36-44W




COLOR TEMPERATURE

3 500K, 4 000K, 5 000K



REMOTE CONTROL
ASD-RC-RC100
Sold separately

luminous intensity distribution diagram



LED STRIPLIGHT FIXTURES

LSF5 with Battery Back-up

Models with a built-in battery back-up ensure 90 minutes of power in case of emergency. The indicator light on the side of the fixture allows you to see whether it is in back-up mode or AC mode.

1950 Lm 12W BATTERY BACK-UP FOR 4FT MODELS

2400 Lm 15W BATTERY BACK-UP FOR 8FT MODELS

 THE INDICATOR ALLOWS YOU TO SEE BACK-UP MODE OR AC MODE

 **PRODUCT SIZES**

4 ft, 8 ft



 **AVAILABLE POWER**

22-28-36-44W
48-68-90W

 **COLOR TEMPERATURE**

3 500K, 4 000K, 5 000K

luminous intensity distribution diagram



LED STRIPLIGHT & STAIRWELL FIXTURES



REMOTE CONTROL
ASD-RC-RC100
Sold separately

LSF5 with Motion Sensor & Battery Back-up

Models with a built-in bi-level microwave Motion Sensor and Battery Back-up are equipped with all optional functions, making them an advanced solution for any commercial application.



AUTOMATIC SWITCH ON/OFF



12W BATTERY BACK-UP



REMOTE CONTROL
Sold separately



PRODUCT SIZES

4 ft



AVAILABLE POWER


22-28-36-44W



COLOR TEMPERATURE

3 500K, 4 000K, 5 000K

luminous intensity distribution diagram



REMOTE CONTROL ASD-RC-RC100

for LSF5 models with Motion Sensor



STAND-BY DIM LEVEL

light output level in stand-by mode

STAND-BY TIME

time the fixture remains at reduced brightness before turning off

AUTO

the sensor starts to function and all settings remain the same as the latest status before the light is switched on/off

HOLD TIME

time the fixture will remain at full brightness after motion is detected

DAYLIGHT SENSOR

the ambient light level that the fixture is set to turn on or off

SEND

upload the selected parameters to sensors

The motion sensor with remote control expands the fixture's capabilities, allowing you to program the lighting and adjust the brightness.

The built-in daylight sensor automatically turns the fixture on or off depending on the ambient light level.

MOUNTING & CONNECTION BRACKETS

This fixture has two different mounting options: suspended and surface. It can easily be suspended using the included V-hook and chains. End entry points make it easy to connect multiple fixtures in line using our connection bracket (sold separately).



SUSPENDED MOUNT V-HOOK
INCLUDED



SURFACE MOUNTING



CONNECTION BRACKET



LED STRIPLIGHT & STAIRWELL FIXTURES



LSF5

Model	Size	Watts	CCT	Lm	Dimensions LxWxH	Pcs. per Carton	Certification
ASD-LSF5-4A44AC-PRM	4 ft	22	3,500 / 4,000 / 5,000	3,205	46-5/8" x 2-1/2" x 2-11/16"	8	UL / DLC PRM
		28		3,969			
		36		5,045			
ASD-LSF5-8A90AC-PRM	8 ft	48	3,500 / 4,000 / 5,000	6,390	92-13/16" x 2-1/2" x 2-11/16"	4	UL / DLC PRM
		68		9,254			
		90		12,534			

LSF5 with Motion Sensor

Model	Size	Watts	CCT	Lm	Dimensions LxWxH	Pcs. per Carton	Certification
ASD-LSF5-4A44AC-MS-SW	4 ft	22	3,500 / 4,000 / 5,000	3,205	46-5/8" x 2-1/2" x 2-11/16"	8	UL / DLC PRM
		28		3,969			
		36		5,045			
		48		6,390			
		68		9,254			
		90		12,534			



LSF5 with Battery Back-up

Model	Size	Watts	CCT	Lm	Dimensions LxWxH	Pcs. per Carton	Certification
ASD-LSF5-4A44AC-12EM-PRM	4 ft	22	3,500 / 4,000 / 5,000	3,205	46-5/8" x 2-1/2" x 2-11/16"	8	UL / DLC PRM
		28		3,969			
		36		5,045			
ASD-LSF5-8A90AC-15EM-PRM	8 ft	48	3,500 / 4,000 / 5,000	6,390	92-13/16" x 2-1/2" x 2-11/16"	4	UL / DLC PRM
		68		9,254			
		90		12,534			

LSF5 with Motion Sensor & Battery Back-up

Model	Size	Watts	CCT	Lm	Dimensions LxWxH	Pcs. per Carton	Certification
ASD-LSF5-4A44AC-12EM-MS-SW	4 ft	22	3,500 / 4,000 / 5,000	3,205	46-5/8" x 2-1/2" x 2-11/16"	8	UL / DLC PRM
		28		3,969			
		36		5,045			
		48		6,390			
		68		9,254			
		90		12,534			



Remote Control for Motion Sensor
ASD-RC-RC100

4-7/8" x 2-3/4" x 3/4"

50



CONNECTION BRACKET

Connection bracket

ACCESSORIES

Model	Applicability	Dimensions LxWxH	Pcs. per Carton
ASD-CB-LSF5	LSF5	5-1/4" x 2-3/4" x 5/8"	100



Connection bracket
ASD-CB-LSF5



Suspended mount v-hook
INCLUDED



J-box mounting plate
INCLUDED



SINCE 1999

ASD LIGHTING CORP



ASD Lighting Corp has become one of the leading LED lighting brands in the United States for commercial and residential applications.

QUALITY

For the production of ASD Luminaires we carefully choose the highest quality components to ensure efficiency and longevity.



LOGISTICS

We are constantly improving our warehouse system so that delivery and storage of ASD products is not only profitable but fast and convenient.

