



Model Number

ASD-LSF8-4A40[WH,BK]-
[BLANK,10EM,QB,QB-10EM]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-KKP1GM



Product Overview

19 fields

CATEGORY

Outdoor Luminaires

GENERAL APPLICATION

Mid Output

PRIMARY USE

Stairwell and Passageway Luminaires

CLASSIFICATION

Premium

TECHNICAL REQUIREMENTS VERSION

6.0

DLC FAMILY CODE

[LLPCPV](#)

BRAND

ASD

PARENT

No

LISTING STATUS

Listed

DATE QUALIFIED
2024-12-16

REPORTED INPUT WATTAGE
38.2 W

REPORTED LIGHT OUTPUT
5,349 lm

REPORTED CCT
3500 K

REPORTED CRI
84

REPORTED R9
13

REPORTED IES RF
85

REPORTED IES RG
96

REPORTED IES RCS,H1
-12

INPUT POWER TYPE
AC

Version History 2 records

2026-06-18	Listed	6	Premium
2024-12-16	Listed	5.1	Premium

V6.0 Controls Options 2 records

QB	1	10V (wired)	Continuo us	10	None	Other	None	None	None	N/A	N/A
[blank]	1	10V (wired)	Continuo us	10	None	Other	None	None	None	N/A	N/A

V5.1 Control Features 6 fields

INTEGRAL CONTROLS
No

DIMMING CAPABILITY AND RANGE

Continuous Dimming to 10% or below

INTEGRAL CONTROL CAPABILITY

No

SENSOR TYPE

No

SSL V5 WIRED COMMUNICATION PROTOCOL

0-10V Analog

SSL V5 WIRELESS COMMUNICATION PROTOCOL

No

Reported Photometric Performance 10 fields**REPORTED LIGHT OUTPUT**

5349 lm

REPORTED EFFICACY (AC)

140 lm/W

REPORTED CCT

3500 K

REPORTED CRI (RA)

84

REPORTED R9

13

REPORTED IES RF

85

REPORTED IES RG

96

REPORTED IES RCS,H1

-12

REPORTED DEFAULT LIGHT OUTPUT

5349 lm

REPORTED BUG RATING

B2 U3 G2

Reported Electrical Performance 5 fields**REPORTED INPUT WATTAGE**

38.2 W

REPORTED TOTAL HARMONIC DISTORTION

15 %

REPORTED POWER FACTOR

0.9

REPORTED DEFAULT INPUT WATTAGE

38.0 W

VOLTAGE RANGE

120-277 V

Tested Photometric Performance No Applicable Data**Tested Electrical Performance** No Applicable Data**LUNA/Turtle Lighting/Amber** No Applicable Data**Field Adjustability** 28 fields**FIELD ADJUSTABLE LIGHT OUTPUT (FALO)**

Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

Light Output	2800 lm	4200 lm	5349 lm	N/A	N/A	N/A	N/A	N/A
Wattage	20 W	30 W	38.21 W	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)

Yes

FACT SETTINGS

3500 K	3500 K	4000 K	5000 K	N/A	N/A	N/A	N/A	N/A
--------	--------	--------	--------	-----	-----	-----	-----	-----

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)

No

Tunability No Applicable Data**Solar** No Applicable Data**Sustainability** No Applicable Data

