

DesignLights Consortium



DLC QPL / Products / Product Details

Model Number

ASD-LSB5B-NEOX-300[BK;WH;BR;SL]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-ZGRJ8T



Product Overview 19 fields

CATEGORY

Outdoor Luminaires

GENERAL APPLICATION

Very High Output

PRIMARY USE

Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

CLASSIFICATION

Premium

TECHNICAL REQUIREMENTS VERSION

6.0

DLC FAMILY CODE

[XXXGBW](#)

BRAND

ASD

PARENT

No

LISTING STATUS

Listed

DATE QUALIFIED

2025-05-05

REPORTED INPUT WATTAGE

302.6 W

REPORTED LIGHT OUTPUT

52,857 lm

REPORTED CCT

3000 K

REPORTED CRI

71

REPORTED R9

-39

REPORTED IES RF

75

REPORTED IES RG

93

REPORTED IES RCS,H1

-17

INPUT POWER TYPE

AC

SPECIFICATION SHEET

[S-ZGRJ8T Specification Sheet](#) Date Updated: 2026-06-29

Version History 2 records

2026-07-10	Listed	6	Premium
2026-05-29	Listed	5.1	Premium

V6.0 Controls Options 1 records

Blank	1	10V (wired)	Continuo us	0	None	Zhaga Book 18	None	None	None	N/A	N/A
-------	---	----------------	----------------	---	------	------------------	------	------	------	-----	-----

V5.1 Control Features 6 fields

INTEGRAL CONTROLS

Yes

DIMMING CAPABILITY AND RANGE

Continuous Dimming to 10% or below

INTEGRAL CONTROL CAPABILITY

No

SENSOR TYPE

Sensor Receptacle, Occupancy Sensing

SSL V5 WIRED COMMUNICATION PROTOCOL

0-10V Analog

SSL V5 WIRELESS COMMUNICATION PROTOCOL

No

Reported Photometric Performance 14 fields

REPORTED LIGHT OUTPUT

52857 lm

REPORTED EFFICACY (AC)

174.7 lm/W

REPORTED CCT

3000 K

REPORTED CRI (RA)

71

REPORTED R9

-39

REPORTED IES RF

75

REPORTED IES RG

93

REPORTED IES RCS,H1

-17

REPORTED MINIMUM LIGHT OUTPUT

34940 lm

REPORTED MAXIMUM LIGHT OUTPUT

52857 lm

REPORTED MINIMUM CCT

3000 K

REPORTED MAXIMUM CCT

5000 K

REPORTED DEFAULT LIGHT OUTPUT

52857 lm

REPORTED BUG RATING

B5 U0 G5

Reported Electrical Performance 7 fields**REPORTED INPUT WATTAGE**

302.6 W

REPORTED TOTAL HARMONIC DISTORTION

9.9 %

REPORTED POWER FACTOR

0.951

REPORTED MINIMUM INPUT WATTAGE

200 W

REPORTED MAXIMUM INPUT WATTAGE

302.6

REPORTED DEFAULT INPUT WATTAGE

302.6 W

VOLTAGE RANGE

120-277 V

Tested Photometric Performance No Applicable Data**Tested Electrical Performance** No Applicable Data**LUNA/Turtle Lighting/Amber** No Applicable Data

Field Adjustability 28 fields

FIELD ADJUSTABLE LIGHT OUTPUT (FALO)
Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

Light Output	34940 lm	41928 lm	52857 lm	N/A	N/A	N/A	N/A	N/A
Wattage	200 W	240 W	302.6 W	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)
Yes

FACT SETTINGS

3000 K	3000 K	4000 K	5000 K	N/A	N/A	N/A	N/A	N/A
--------	--------	--------	--------	-----	-----	-----	-----	-----

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)
No

Tunability No Applicable Data

Solar No Applicable Data

Sustainability No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number