

DesignLights Consortium



DLC QPL / Products / Product Details

Model Number

ASD-WLR-60[BK,BR]-[PC,PC-UD]-[Blank,EM]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-RQ0LNP



Product Overview 19 fields

CATEGORY

Outdoor Luminaires

GENERAL APPLICATION

Mid Output

PRIMARY USE

Outdoor Uplight-Emitting Wall-Mounted Area Luminaire

CLASSIFICATION

Premium

TECHNICAL REQUIREMENTS VERSION

6.0

DLC FAMILY CODE

[JNJCLW](#)

BRAND

ASD

PARENT

Yes

LISTING STATUS

Listed

DATE QUALIFIED

2025-05-23

REPORTED INPUT WATTAGE

60.9 W

REPORTED LIGHT OUTPUT

8,234 lm

REPORTED CCT

3000 K

REPORTED CRI

82

REPORTED R9

4

REPORTED IES RF

83

REPORTED IES RG

98

REPORTED IES RCS,H1

-11

INPUT POWER TYPE

AC

SPECIFICATION SHEET

[S-RQ0LNP Specification Sheet](#) Date Updated: 2026-06-29

Version History 2 records

2026-07-11	Listed	6	Premium
2025-05-23	Listed	5.1	Premium

V6.0 Controls Options 2 records

PC	3B	10V (wired)	Continuo us	10	None	None	None	Photocel l only	Light- depende nt Resistor	N/A	N/A
[blank]	1	10V (wired)	Continuo us	10	None	Other	None	None	None	N/A	N/A

V5.1 Control Features 6 fields

INTEGRAL CONTROLS

Yes

DIMMING CAPABILITY AND RANGE

Continuous Dimming to 10% or below

INTEGRAL CONTROL CAPABILITY

No

SENSOR TYPE

Exterior Photocell

SSL V5 WIRED COMMUNICATION PROTOCOL

0-10V Analog

SSL V5 WIRELESS COMMUNICATION PROTOCOL

No

Reported Photometric Performance 14 fields

REPORTED LIGHT OUTPUT

8234 lm

REPORTED EFFICACY (AC)

135.27 lm/W

REPORTED CCT

3000 K

REPORTED CRI (RA)

82

REPORTED R9

4

REPORTED IES RF

83

REPORTED IES RG

98

REPORTED IES RCS,H1

-11

REPORTED MINIMUM LIGHT OUTPUT

5411 lm

REPORTED MAXIMUM LIGHT OUTPUT

8234 lm

REPORTED MINIMUM CCT

3000 K

REPORTED MAXIMUM CCT

5000 K

REPORTED DEFAULT LIGHT OUTPUT

8234 lm

REPORTED BUG RATING

B3 U3 G1

Reported Electrical Performance 7 fields

REPORTED INPUT WATTAGE

60.9 W

REPORTED TOTAL HARMONIC DISTORTION

15 %

REPORTED POWER FACTOR

0.9

REPORTED MINIMUM INPUT WATTAGE

40 W

REPORTED MAXIMUM INPUT WATTAGE

60.9

REPORTED DEFAULT INPUT WATTAGE

60.9 W

VOLTAGE RANGE

120-277 V

Tested Photometric Performance 10 fields

TESTED VOLTAGE FOR MINIMUM EFFICACY

120

TESTED LIGHT OUTPUT

8234 lm

TESTED EFFICACY (AC)

135.27 lm/W

TESTED CCT

3019 K

TESTED CRI (RA)

82

TESTED R9

4

TESTED IES RF

83

TESTED IES RG

98

TESTED IES RCS,H1

-11 %

TESTED DUV

-0.0008

Tested Electrical Performance 3 fields**TESTED INPUT WATTAGE**

60.87 W

TESTED TOTAL HARMONIC DISTORTION

3.8 %

TESTED POWER FACTOR

0.976

LUNA/Turtle Lighting/Amber No Applicable Data**Field Adjustability** 28 fields**FIELD ADJUSTABLE LIGHT OUTPUT (FALO)**

Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

Light Output	5410.8 lm	6763.5 lm	8234 lm	N/A	N/A	N/A	N/A	N/A
Wattage	40 W	50 W	60.9 W	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)

Yes

FACT SETTINGS

3000 K	3000 K	4000 K	5000 K	N/A	N/A	N/A	N/A	N/A
--------	--------	--------	--------	-----	-----	-----	-----	-----

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)
No

Tunability No Applicable Data

Solar No Applicable Data

Sustainability No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number