



LED UFO HIGH BAY

*The best solution
for warehouse lighting*



PRODUCT PRESENTATION | 2023

WWW.ASD-LIGHTING.COM



LED UFO HIGH BAY



Q-BASE LED UFO HIGH BAY
page 6



Q-BASE LED UFO HIGH BAY HIGH VOLTAGE
page 7



LED UFO HIGH BAY
page 12


ACCESSORIES:



Q-BASE MOTION SENSOR FOR UHB3
page 8



MOTION SENSOR KIT FOR UHB2
page 13



BATTERY BACK-UP KIT
page 14



MOUNTING BRACKETS & HOOKS
page 15



REFLECTORS & LENSES
page 17



LED UFO HIGH BAY

APPLICATION

This light is the perfect commercial or industrial solution for warehouses, supermarkets, retail stores, gyms, garages, general task areas and many other applications. This fixture is IP69K rated and is resistant to high pressure, temperature, water and dust.

ENERGY SAVING & EFFICIENCY


This fixture will save you a significant amount of money in its lifetime by providing high lumen output with low energy consumption.

CERTIFICATION & WARRANTY

ASD provides a 5-year warranty along with UL and DLC Premium certifications to guarantee top quality products and safety, which allows for participation in rebates.



*The best solution
for warehouse lighting*



Q-BASE LED UFO HIGH BAY

UHB3

Q-BASE LED UFO HIGH BAY has a built-in Motion Sensor base, allowing for easy installation of our Microwave or PIR Motion Sensor.

Die-cast aluminum housing with excellent heat dissipation along with an anti-glare PC Lens provide many years of use.

This fixture is also CCT selectable, allowing you to set it to either 3,000K, 4,000K, or 5,000K with a simple switch. It is also power adjustable, allowing you to change the light output with a simple switch.



HIGH VOLTAGE MODELS

Q-BASE LED UFO HIGH BAY HIGH VOLTAGE has a professional energy-efficient LED driver to ensure high performance and protection against water and dust at 277-480V. Power adjustable and CCT selectable options allow for flexibility and suitability in different professional projects and sites.

MICROWAVE & INFRARED MOTION SENSORS

The field-installed Motion Sensor ensures higher energy savings and provides increased light control. Two different Motion Sensors are available for different site environments.

BATTERY BACK-UP KIT

The Battery Back-Up Kit ensures 90 minutes of power in case of emergency. We offer 40W and 60W models as well as a High Voltage option to provide compatibility for our entire LED UFO series.

DRIVER

Energy-efficient 0-10V dimmable LED driver provides stable light output with economic power consumption

HOUSING

Durable aluminum housing protects fixture from mechanical damage, water and dust

RUBBER RING

Provides reliable isolation, increased tightness and protection from moisture and dust

PC LENS

Polycarbonate lens is impact-resistant and extremely tough, providing smooth light distribution

COATING

Coated with powder paint to protect against oxidation and corrosion

LED LENS

Highly efficient LEDs provide more than 150lm/W output

MS BASE

Built-in base for easy Motion Sensor installation any time by simple twist-in



Q-BASE LED UFO HIGH BAY

UHB3

Power Adjustable and Color Selectable

Q-BASE LED UFO HIGH BAY has a built-in Motion Sensor base, allowing you to install the Microwave Motion Sensor or PIR Sensor. Die-cast aluminum housing with excellent heat dissipation along with an anti-glare PC lens provide many years of use.

This fixture is also CCT selectable, allowing you to set it to either 3,000K, 4,000K or 5,000K with a simple switch. It is also power adjustable, allowing you to change the light output with a simple switch.

W POWER ADJUSTABLE



60W-500W

3CCT COLOR SELECTABLE

3000K, 4000K, 5000K

-  BUILT-IN MOTION SENSOR BASE
-  -40°F TO 149°F FOR A WIDE VARIETY OF APPLICATIONS
-  COLOR AND POWER SELECTABLE
-  IP69K RATED, ALLOWS HIGH PRESSURE WASHING

luminous intensity distribution diagram



White Black

-  120-277V voltage
-  0-10V dimming
-  6kV Surge protection
-  Wet locations



PIR MOTION SENSOR
HD09VR-PH

MICROWAVE MOTION SENSOR
HD09VR-MH

REMOTE CONTROL
for Motion Sensor
HD05R

Q-BASE LED UFO HIGH BAY

UHB3 High Voltage

Q-BASE LED UFO HIGH BAY HIGH VOLTAGE has a professional energy-efficient LED driver to ensure high performance and protection against water and dust at 277-480V.

Power adjustable and CCT selectable options allow for flexibility and suitability in different professional projects and sites.



150W-500W



3CCT, 5000K



BUILT-IN MOTION SENSOR BASE



-40°F TO 149°F FOR A WIDE VARIETY OF APPLICATIONS







SURGE PROTECTION AGAINST VOLTAGE SPIKES AND CURRENT SURGES



IP69K RATED, ALLOWS HIGH PRESSURE WASHING

luminous intensity distribution diagram



PIR MOTION SENSOR
HD09VR-PH



MICROWAVE MOTION SENSOR
HD09VR-MH



REMOTE CONTROL
for Motion Sensor
HD05R





Q-BASE MOTION SENSOR



MOTION SENSOR HEIGHT 49.21ft MAX



DAYLIGHT HARVESTING



Microwave Motion Sensor

HD09VR-MH

Microwave Sensors are used in places not tightly packed with metal structures and also where the ambient temperature is close to the temperature of the human body.

Moving objects or people will trigger the sensor.



PIR Motion Sensor

HD09VR-PH

PIR Sensors can be used in places densely packed with metal structures. The sensor is less sensitive when there is not much difference between the human body and the environment temperature.

The movement of heat or warmth will trigger the sensor (humans, animals, etc.), while the movement of inanimate objects will not (such as movement caused by machines or wind).



REMOTE CONTROL
HD05R for both models
(sold separately)

The field-installed Motion Sensor is easy to install directly into the fixture's Q-BASE, ensuring higher energy savings and increased light control. Installation is as easy as just screwing it into the Q-BASE. No wiring necessary.

Both Microwave and PIR Motion Sensors are available for different site environments for all ASD Q-BASE products.

■ SETTINGS

Detection Range (max 15m)	25%, 50%, 75%, 100%
Hold Time	5s, 30s, 1min, 3min, 5min, 10min, 20min, 30min
Daylight Threshold	Disable, 2lux, 10lux, 30lux, 50lux, 80lux, 120lux
Standby Dim Level	10%, 20%, 30%, 50%
Stand-by Time	0s, 10s, 30s, 1min, 5min, 10min, 30min, 60min+

■ APPLICATION



UHB3



WHB5A



CAN07A

REMOTE CONTROL

HD05R

for PIR and MW
Motion Sensors

DETECTION RANGE
sensitivity of Motion Sensor



STAND-BY TIME
time the fixture remains at reduced
brightness before turning off



HOLD TIME
time the fixture will remain at full
brightness after motion is detected



STAND-BY DIM LEVEL
light output level in stand-by mode



DAYLIGHT THRESHOLD
the ambient light level that the fixture
is set to turn on or off



One remote can control both types of Motion Sensor, in addition to giving you access to lighting and brightness settings, expanding the capabilities of the fixture.



Scene
SCENE
shows current settings
saved in remote

Start
START
press this to begin scene setup

Memory
MEMORY
saves the scene settings

Apply
APPLY
applies current scene settings
to the fixture

Both models have a built-in daylight sensor that automatically turns the fixture on and off depending on the ambient light level.

LED UFO HIGH BAY

UHB2

LED UFO HIGH BAYS are extremely efficient with a 150lm/W output and can operate in temperatures between -40 to 149°F (-40 to 65°C), allowing them to be utilized in a wide variety of applications.



MOTION SENSOR KIT

The field-installed Motion Sensor ensures higher energy savings and provides increased light control.

BATTERY BACK-UP KIT

The 40W Back-Up ensures 90 minutes of power in case of emergency and is also equipped with an automatic self-checking option and remote (sold separately) to test.

CORD

4 ft cord allows for easy installation

DRIVER

Energy-efficient 0-10V dimmable LED driver provides stable light output with economic power consumption

HOUSING

Durable aluminum housing protects fixture from mechanical damage, water and dust

RUBBER RING

Provides reliable isolation, increased tightness and protection from moisture and dust

MOUNTING RING

The UFO HIGH BAY is equipped with a mounting ring. 400W and 500W models are equipped with a spring hook and surface bracket.

COATING

Coated with powder paint to protect against oxidation and corrosion

LED LENS

Highly efficient LEDs provide more than 150lm/W output

TEMPERED GLASS

Tempered glass lens is impact-resistant and extremely tough, providing smooth light distribution



LED UFO HIGH BAY

UHB2

LED UFO HIGH BAYS are extremely efficient with a 150lm/W output and can operate in temperatures between -40 to 149°F (-40 to 65°C), allowing them to be utilized in a wide variety of applications.

W AVAILABLE POWER

100W, 150W, 200W, 240W, 300W, 500W

K COLOR TEMPERATURE

5000K



W DIE-CAST ALUMINUM HOUSING WITH EXCELLENT HEAT DISSIPATION

W -40°F TO 149°F FOR A WIDE VARIETY OF APPLICATIONS


W SURGE PROTECTION AGAINST VOLTAGE SPIKES AND CURRENT SURGES

W IP69K RATED, ALLOWS FOR HIGH PRESSURE WASHING


luminous intensity distribution diagram




100W
150W
200W



240W
300W



500W



120-277V voltage



1-10V dimming



Wet locations



MOTION SENSOR

The field-installed Motion Sensor ensures higher energy savings and provides increased light control.

Two different Motion Sensor kits are available for Regular and High Voltage models.



MOUNTING HEIGHT UP TO 49.2FT MAX



DAYLIGHT THRESHOLD



ADJUSTABLE STAND-BY TIME



REMOTE CONTROL
Sold separately



120-277V voltage




Wet locations



Motion sensor kit can be installed directly on fixture or PC reflector



REMOTE CONTROL
UHB-RC-MSK1
for Regular Voltage MS





BATTERY BACK-UP KIT

The Battery Back-Up Kit ensures 90 minutes of power in case of emergency. We offer 40W and 60W models as well as a High Voltage option to provide compatibility for our entire LED UFO series.

It is also equipped with an automatic self checking option and a remote to test.



MORE THAN 6 000LM IN EMERGENCY MODE FOR 90MIN



AUTOMATIC SELF-CHECKING OPTION



THE INDICATOR ALLOWS YOU TO SEE BACK-UP MODE OR AC MODE



REMOTE TEST SWITCH Sold separately



Battery Back-Up Kit with integrated junction box

BLD-RM40R / BLD-RM60R

for UHB2, UHB3 100-300W / for UHB2, UHB3 100-500W



Battery Back-Up Kit

BLD-GM60R-HV

UHB3HV 100-500W



REMOTE TEST SWITCH RN1
for all models




MOUNTING BRACKETS & HOOKS

These fixtures have three different mounting options: suspended, surface, and pendant.



SCREW-BOLT HOOK



SPRING HOOK



PENDANT MOUNT BRACKET



PENDANT MOUNT BRACKET WITH JUNCTION BOX

SURFACE MOUNTING BRACKETS



SURFACE MOUNT BRACKET
FOR UHB3 100W-300W



SURFACE MOUNT BRACKET
FOR UHB3 400W-500W



SURFACE MOUNT BRACKET
FOR UHB2 100W-300W



REFLECTORS AND LENSES

Focus your light using different types of polycarbonate reflectors and lenses (sold separately).



POLYCARBONATE REFLECTORS
16" or 19"




POLYCARBONATE BOTTOM CONICAL LENS
16" or 19"





LED Q-BASE UFO HIGH BAY



UHB3 POWER ADJUSTABLE AND COLOR SELECTABLE

Model	Watts	Input Voltage	Dimmable	CCT	Lm	Finish	Dimensions DxH	Pcs. per Carton	Certification
ASD-UHB3-100ADAC-BK	60W 80W 100W	120-277V	0-10V	3000K/4000K/5000K	9,559lm 12,354lm 14,603lm	Black	10-1/4" x 6-7/16"	1	UL / DLC PRM
ASD-UHB3-150ADAC-WH	100W 120W 150W	120-277V	0-10V	3000K/4000K/5000K	15,974lm 18,615lm 21,521lm	White	10-1/4" x 6-7/16"	1	UL / DLC PRM
ASD-UHB3-150ADAC-BK	100W 120W 150W	120-277V	0-10V	3000K/4000K/5000K	15,974lm 18,615lm 21,521lm	Black	10-1/4" x 6-7/16"	1	UL / DLC PRM
ASD-UHB3-200ADAC-WH	100W 150W 200W	120-277V	0-10V	3000K/4000K/5000K	16,255lm 23,468lm 30,407lm	White	12-5/8" x 6-15/16"	1	UL / DLC PRM
ASD-UHB3-200ADAC-BK	100W 150W 200W	120-277V	0-10V	3000K/4000K/5000K	16,255lm 23,468lm 30,407lm	Black	12-5/8" x 6-15/16"	1	UL / DLC PRM
ASD-UHB3-240ADAC-BK	150W 200W 240W	120-277V	0-10V	3000K/4000K/5000K	24,541lm 31,243lm 34,912lm	Black	12-5/8" x 6-15/16"	1	UL / DLC PRM
ASD-UHB3-300ADAC-BK	200W 240W 300W	120-277V	0-10V	3000K/4000K/5000K	30,977lm 35,304lm 40,913lm	Black	12-5/8" x 7-11/16"	1	UL / DLC PRM
ASD-UHB3-500ADAC-BK	300W 400W 500W	120-277V	0-10V	3000K/4000K/5000K	47,548lm 59,570lm 69,777lm	Black	16-9/16" x 9-1/8"	1	UL / DLC PRM

UHB3 High Voltage

Model	Watts	Input Voltage	Dimmable	CCT	Lm	Finish	Dimensions DxH	Pcs. per Carton	Certification
ASD-UHB3HV-150D50-BK	150W	277-480V	0-10V	5000K	22,200lm	Black	10-1/4" x 6-7/16"	1	UL / DLC PRM
ASD-UHB3HV-200D50-BK	200W	277-480V	0-10V	5000K	29,600lm	Black	12-5/8" x 6-13/16"	1	UL / DLC PRM
ASD-UHB3HV-300ADAC-BK	200W 240W 300W	277-480V	0-10V	3000K/4000K/5000K	28,531lm 32,942lm 39,042lm	Black	12-5/8" x 7-11/16"	1	UL / DLC PRM
ASD-UHB3HV-500ADAC-BK	300W 400W 500W	277-480V	0-10V	3000K/4000K/5000K	47,247lm 59,701lm 70,715lm	Black	16-9/16" x 10-3/8"	1	UL / DLC PRM

UHB2



Model	Watts	Input Voltage	Dimmable	CCT	Lm	Finish	Dimensions DxH	Pcs. per Carton	Certification
ASD-UHB2-100D50-PRM	100W	120-277V	1-10V	5000K	14,800lm	Black	10-1/4" x 6-1/4"	1	UL / DLC PRM
ASD-UHB2-150D50W-PRM	150W	120-277V	1-10V	5000K	22,200lm	White	10-1/4" x 6-7/8"	1	UL / DLC PRM
ASD-UHB2-150D50-PRM	150W	120-277V	1-10V	5000K	22,200lm	Black	10-1/4" x 6-7/8"	1	UL / DLC PRM
ASD-UHB2-200D50W-PRM	200W	120-277V	1-10V	5000K	29,600lm	White	10-1/4" x 6-7/8"	1	UL / DLC PRM
ASD-UHB2-200D50-PRM	200W	120-277V	1-10V	5000K	29,600lm	Black	10-1/4" x 6-7/8"	1	UL / DLC PRM
ASD-UHB2-240D50-PRM	240W	120-277V	1-10V	5000K	35,520lm	Black	12-5/8" x 6-3/4"	1	UL / DLC PRM
ASD-UHB2-300D50-PRM	300W	120-277V	0-10V	5000K	45,000lm	Black	12-5/8" x 7-13/16"	1	UL / DLC PRM
ASD-UHB2-500D50-PRM	500W	120-277V	0-10V	5000K	75,000lm	Black	14-3/16" x 9-1/4"	1	UL / DLC PRM

Q-BASE MOTION SENSOR

Microwave Motion Sensor
PIR Motion Sensor
Remote Control for Motion Sensor

ACCESSORIES

Model	Applicable Models	Dimensions LxWxH	Pcs. per Carton
HD09VR-MH	UHB3	2-1/8" x 2-1/8" x 1-5/16"	120
HD09VR-PH	UHB3	2-1/8" x 2-1/8" x 1-5/8"	120
HD05R	HD09VR-PH, HD09VR-MH	5-1/2" x 2-5/16" x 7/8"	78





LED UFO HIGH BAY ACCESSORIES

MOTION SENSOR

ACCESSORIES

	Model	Applicable Models	Input Voltage	Dimensions LxWxH	Pcs. per Carton
Motion Sensor Kit	UHB-MSK1	UHB2	120-277V	5-5/8" x 3-1/2" x 2-15/16"	40
Remote Control for UHB-MSK1	UHB-RC-MSK1	UHB-MSK1	-	6-7/8" x 2-1/4" x 11/16"	100



BATTERY BACK-UP KIT

ACCESSORIES


	Model	Applicable Models	Watts	Dimensions LxWxH	Pcs. per Carton
Battery Back-Up	BLD-RM40R	UHB2, UHB3 100-300W	40W	15-11/16" x 15-11/16" x 5-9/16"	4
	BLD-RM60R	UHB2, UHB3 100-500W	60W	10-13/16" x 57-9/16" x 57-9/16"	4
	BLD-GM60R-HV	UHB3HV 100-500W	60W	14-1/2" x 3-1/16" x 1-7/8"	5
Remote Test Switch for Battery Back-Up	RN1	BLD-RM40R, BLD-RM60R, BLD-GM60R-HV	-	5-1/8" x 1-1/4" x 5/8"	20



REFLECTORS & LENSES

ACCESSORIES

	Model	Applicable Models	Finish	Dimensions DxH	Pcs. per Carton
Polycarbonate Reflector	ASD-DUHB-16-90PC	UHB2	Clear	16-1/4" x 3-7/8"	10
	ASD-DUHB-19-90PC	UHB2	Clear	18-7/8" x 5-1/2"	10
Polycarbonate Bottom Conical Lens	ASD-BLUHB-16PC	ASD-DUHB-16-90PC	Clear	15-15/16" x 1-1/4"	10
	ASD-BLUHB-19PC	ASD-DUHB-19-90PC	Clear	18-11/16" x 1-7/8"	10





LED UFO HIGH BAY MOUNTING OPTIONS

MOUNTING BRACKETS & HOOKS

ACCESSORIES

Model	Applicable Models	Finish	Dimensions LxWxH	Pcs. per Carton
Spring Hook ASD-H-M10 ASD-H-M12	UHB2, UHB3 100-240W UHB2, UHB3 300W	- -	3-5/16" x 2-1/8" x 7/8" 3-1/2" x 2-5/16" x 1"	50 50
Screw-bolt Hook ASD-HS-M10	UHB2, UHB3 100-240W	-	3-7/8" x 1-5/8" x 1-1/4"	50
Pendant Mount Bracket ASD-PMB-UHB	UHB2, UHB3 100-300W	Black	2-3/8" x 1-1/2" x 2-7/8"	50
Pendant Mount Bracket with J-box and Spring hook ASD-PMBJB-UHB	UHB2, UHB3 100-300W	Black	4-3/4" x 5-1/16" x 7-3/16"	20
Surface Mount Bracket ASD-SMB1-UHB3-WH ASD-SMB1-UHB3-BK	UHB3 100-300W UHB3 100-300W	White Black	10-1/16" x 6-11/16" x 2-5/8" 10-1/16" x 6-11/16" x 2-5/8"	20 20
ASD-SMB2-UHB3-BK	UHB3 400-500W	Black	12-5/15" x 8-1/4" x 2-5/8"	20
ASD-SMB100/300-UHB2W ASD-SMB100/300-UHB2	UHB2 100-300W UHB2 100-300W	White Black	9-11/16" x 6-5/16" x 2-3/8" 9-11/16" x 6-5/16" x 2-3/8"	20 20



Spring Hook
ASD-H-M10
ASD-H-M12



Screw-bolt Hook
ASD-HS-M10




Pendant Mount Bracket
ASD-PMB-UHB



Pendant Mount Bracket with J-box and Spring hook
ASD-PMBJB-UHB



Surface Mount Bracket for UHB3 100W-300W
ASD-SMB1-UHB3-BK
ASD-SMB1-UHB3-WH



Surface Mount Bracket for UHB3 400W-500W
ASD-SMB2-UHB3-BK



Surface Mount Bracket for UHB2
ASD-SMB100/300-UHB2
ASD-SMB100/300-UHB2W





SINCE 1999

ASD LIGHTING CORP



ASD Lighting Corp has become one of the leading LED lighting brands in the United States for commercial and residential applications.

QUALITY

For the production of ASD Luminaires we carefully choose the highest quality components to ensure efficiency and longevity.



LOGISTICS

We are constantly improving our warehouse system so that delivery and storage of ASD products is not only profitable but fast and convenient.

