

DesignLights Consortium



Model Number	ASD-WLP01SL-A60[BK;WH;NK;BR]-PC
Classification	Premium
Primary Use	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires
Reported Input Wattage	55.2 W
Reported Light Output	7395 lm
Reported CCT	3000 K
Reported CRI (Ra)	83
Product ID	S-2Q9RLQ
DLC Family Code	BCBADI
Listing Status	Listed
Date Qualified	2024-04-08

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-2Q9RLQ
Manufacturer	ASD Lighting Corp
Brand	ASD
Model Number	ASD-WLP01SL-A60[BK;WH;NK;BR]-PC
Parent	Yes
Classification	Premium
DLC Family Code	BCBADI
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Mid Output
Primary Use Designation	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wired Communication Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	7395 lm
Reported Efficacy (AC)	133.9 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	83
Reported R9	8
Reported IES Rf	85
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Minimum Light Output	3750 lm
Reported Maximum Light Output	7395 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	7395 lm
Reported BUG Rating	B1 U4 G3

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	55.2 W
Reported Total Harmonic Distortion	14.9 %
Reported Power Factor	0.88
Reported Minimum Input Wattage	30 W
Reported Maximum Input Wattage	55.2
Reported Default Input Wattage	55.2 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	7395 lm
Tested Efficacy (AC)	133.87 lm/W

Tested CCT	3143 K
Tested CRI (Ra)	83
Tested R9	8
Tested IES Rf	85
Tested IES Rg	97
Tested IES Rcs,h1	-11 %
Tested Duv	-0.0004
Tested Backlight (TM-15 BUG)	1
Tested BUG Rating	B1 U4 G3

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	55.2 W
Tested Total Harmonic Distortion	14.9 %
Tested Power Factor	0.884

VERSION HISTORY VIEW DETAILS

2024-05-17	Listed	5.1	Premium
------------	--------	-----	---------