


DesignLights Consortium



Model Number	ASD-BLP-24A67-4P (BLANK/QB/8EM/MS)
Classification	Standard
Primary Use	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	67 W
Reported Light Output	9782 lm
Reported CRI (Ra)	80
Product ID	S-3KSGSL
DLC Family Code	PZDGBL
Listing Status	Listed
Date Qualified	2026-04-29
Reported CCT	3000 K
Specification Sheet	S-3KSGSL Specification Sheet Date Updated: 2026-04-13

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	6.0
Product ID	S-3KSGSL
Manufacturer	ASD Lighting Corp
Brand	ASD
Model Number	ASD-BLP-24A67-4P (BLANK/QB/8EM/MS)
Parent	Yes
Classification	Standard
DLC Family Code	PZDGBL
Input Power Type	AC
Field Adjustable Color Temperature	Yes
Solar	No

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer

Primary Use Designation	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Warm-Dimming	No

V5.1 CONTROL FEATURES VIEW DETAILS

Integral Control Capability	No
-----------------------------	----

V6.0 CONTROLS OPTIONS VIEW DETAILS

Under Review

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	9782 lm
Reported Efficacy (AC)	146 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	80
Reported R9	0
Reported IES Rf	83
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Default Light Output	9782 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	67 W
Reported Total Harmonic Distortion	7.9 %
Reported Power Factor	0.976
Reported Default Input Wattage	67 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	10028 lm
Tested Efficacy (AC)	146.53 lm/W
Tested CCT	3003 K
Tested CRI (Ra)	80
Tested R9	0
Tested IES Rf	83
Tested IES Rg	94

Tested IES Rcs,h1	-13 %
Tested Duv	-0.0001

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	68.44 W
Tested Total Harmonic Distortion	8.3 %
Tested Power Factor	0.976

FIELD ADJUSTABILITY VIEW DETAILS

Field Adjustable Light Output	Yes
Field Adjustable Light Distribution	No
Reported Light Output Setting 1	6004 lm
Reported Wattage Setting 1	38 W
Reported Light Output Setting 2	6930 lm
Reported Wattage Setting 2	45 W
Reported Light Output Setting 3	7650 lm
Reported Wattage Setting 3	51 W
Reported Light Output Setting 4	9782 lm
Reported Wattage Setting 4	67 W
Reported Default CCT	3000
Reported CCT Setting 1	3000
Reported CCT Setting 2	3500
Reported CCT Setting 3	4000
Reported CCT Setting 4	5000
Reported CCT Setting 5	6500
Aimable	No
Levelable	No

TUNABILITY VIEW DETAILS

CCT-Tunable	No
Full Color-Tunable	No

VERSION HISTORY VIEW DETAILS

2026-04-29	Listed	6	Standard
------------	--------	---	----------

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number