

DesignLights Consortium



DLC QPL / Products / Product Details

Model Number

ASD-UHB2AHV-NEOX-150[BK;WH;BR;SL]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Premium

Product ID: S-RXT93W



Product Overview 19 fields

CATEGORY

Indoor Luminaires

GENERAL APPLICATION

High-Bay

PRIMARY USE

High-Bay Luminaires for Commercial and Industrial Buildings

CLASSIFICATION

Premium

TECHNICAL REQUIREMENTS VERSION

6.0

DLC FAMILY CODE

[WWWYIJ](#)

BRAND

ASD

PARENT

No

LISTING STATUS

Listed

DATE QUALIFIED

2025-07-10

REPORTED INPUT WATTAGE

151.1 W

REPORTED LIGHT OUTPUT

26,916 lm

REPORTED CCT

3000 K

REPORTED CRI

71

REPORTED R9

-39

REPORTED IES RF

75

REPORTED IES RG

92

REPORTED IES RCS,H1

-17

INPUT POWER TYPE

AC

SPECIFICATION SHEET

[S-RXT93W Specification Sheet](#) Date Updated: 2026-07-09

Version History

2 records

2026-07-10	Listed	6	Premium
2025-07-10	Listed	5.1	Premium

V6.0 Controls Options 1 records

Blank	1	10V (wired)	Continuo us	0	None	Zhaga Book 18	None	None	None	N/A	N/A
-------	---	----------------	----------------	---	------	------------------	------	------	------	-----	-----

V5.1 Control Features 6 fields

INTEGRAL CONTROLS

No

DIMMING CAPABILITY AND RANGE

Continuous Dimming to 10% or below

INTEGRAL CONTROL CAPABILITY

No

SENSOR TYPE

No

SSL V5 WIRED COMMUNICATION PROTOCOL

0-10V Analog

SSL V5 WIRELESS COMMUNICATION PROTOCOL

No

Reported Photometric Performance 13 fields

REPORTED LIGHT OUTPUT

26916 lm

REPORTED EFFICACY (AC)

178.1 lm/W

REPORTED CCT

3000 K

REPORTED CRI (RA)

71

REPORTED R9

-39

REPORTED IES RF

75

REPORTED IES RG

92

REPORTED IES RCS,H1

-17

REPORTED MINIMUM LIGHT OUTPUT

17813 lm

REPORTED MAXIMUM LIGHT OUTPUT

26916 lm

REPORTED MINIMUM CCT

3000 K

REPORTED MAXIMUM CCT

5000 K

REPORTED DEFAULT LIGHT OUTPUT

26916 lm

Reported Electrical Performance 7 fields**REPORTED INPUT WATTAGE**

151.1 W

REPORTED TOTAL HARMONIC DISTORTION

7 %

REPORTED POWER FACTOR

0.915

REPORTED MINIMUM INPUT WATTAGE

100 W

REPORTED MAXIMUM INPUT WATTAGE

151.1

REPORTED DEFAULT INPUT WATTAGE

151.1 W

VOLTAGE RANGE

200-480 V

Tested Photometric Performance No Applicable Data**Tested Electrical Performance** No Applicable Data**Indoor Amber** No Applicable Data**Field Adjustability** 28 fields

FIELD ADJUSTABLE LIGHT OUTPUT (FALO)

Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

Light Output	17810 lm	21372 lm	26916 lm	N/A	N/A	N/A	N/A	N/A
Wattage	100 W	120 W	151.1 W	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)

Yes

FACT SETTINGS

3000 K	3000 K	4000 K	5000 K	N/A	N/A	N/A	N/A	N/A
--------	--------	--------	--------	-----	-----	-----	-----	-----

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)

No

Tunability No Applicable Data

Solar No Applicable Data

Sustainability No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number