

# DesignLights Consortium



Model Number	ASD-WLR-60[BK,BR]-[PC,PC-UD]-[Blank,EM]
Classification	Premium
Primary Use	Outdoor Full-Cutoff Wall-Mounted Area Luminaires
Reported Input Wattage	60.9 W
Reported Light Output	8234 lm
Reported CCT	3000 K
Reported CRI (Ra)	82
Product ID	S-RQ0LNP
DLC Family Code	<a href="#">JNJCLW</a>
Listing Status	Listed
Date Qualified	2025-05-23

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-RQ0LNP
Manufacturer	ASD Lighting Corp
Brand	ASD
Model Number	ASD-WLR-60[BK,BR]-[PC,PC-UD]-[Blank,EM]
Parent	Yes
Classification	Premium
DLC Family Code	JNJCLW
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Mid Output
Primary Use Designation	Outdoor Full-Cutoff Wall-Mounted Area Luminaires

## CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No
Sensor Type	Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	8234 lm
Reported Efficacy (AC)	135.27 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	82
Reported R9	4
Reported IES Rf	83
Reported IES Rg	98
Reported IES Rcs,h1	-11
Reported Minimum Light Output	5411 lm
Reported Maximum Light Output	8234 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	8234 lm
Reported BUG Rating	B3 U3 G1

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	60.9 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	40 W
Reported Maximum Input Wattage	60.9
Reported Default Input Wattage	60.9 W
Voltage Range	120-277 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	8234 lm
Tested Efficacy (AC)	135.27 lm/W
Tested CCT	3019 K

Tested CRI (Ra)	82
Tested R9	4
Tested IES Rf	83
Tested IES Rg	98
Tested IES Rcs,h1	-11 %
Tested Duv	-0.0008

### TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	60.87 W
Tested Total Harmonic Distortion	3.8 %
Tested Power Factor	0.976

### VERSION HISTORY VIEW DETAILS

2025-05-23	Listed	5.1	Premium
------------	--------	-----	---------