Model Number

ASD-LSF8-8A80[WH,BK]-[BLANK,15EM,QB,QB-15EM]

Manufacturer

ASD Lighting Corp

Brand

ASD

SSL V6.0 Premium

SSL V5.1 Standard

Product ID: S-KBVC5K

Product Overview 19 fields

CATEGORY
Indoor Luminaires

GENERAL APPLICATION
Linear Ambient

PRIMARY USE
Direct Linear Ambient Luminaires

CLASSIFICATION
Premium

TECHNICAL REQUIREMENTS VERSION
6.0

DLC FAMILY CODE
LLLCPV

BRAND
ASD

PARENT
No

LISTING STATUS
Listed

DATE QUALIFIED
2024-12-16

REPORTED INPUT WATTAGE
78.9 W

REPORTED LIGHT OUTPUT
11,046 lm

REPORTED CCT
3500 K

REPORTED CRI
83

REPORTED R9
10

REPORTED IES RF
84

REPORTED IES RG
95

REPORTED IES RCS,H1
-12

INPUT POWER TYPE
AC

Version History 2 records

2026-06-18	Listed	6	Premium
2024-12-16	Listed	5.1	Standard

V6.0 Controls Options 2 records

QB	**1**	10V (wired)	Continuous	10	None	Other	None	None	None	N/A	N/A
[blank]	**1**	10V (wired)	Continuous	10	None	Other	None	None	None	N/A	N/A

V5.1 Control Features 6 fields

INTEGRAL CONTROLS
No

DIMMING CAPABILITY AND RANGE
Continuous Dimming to 10% or below

INTEGRAL CONTROL CAPABILITY
No

SENSOR TYPE
No

SSL V5 WIRED COMMUNICATION PROTOCOL
0-10V Analog

SSL V5 WIRELESS COMMUNICATION PROTOCOL
No

Reported Photometric Performance 9 fields

REPORTED LIGHT OUTPUT
11046 lm

REPORTED EFFICACY (AC)
140 lm/W

REPORTED CCT
3500 K

REPORTED CRI (RA)
83

REPORTED R9
10

REPORTED IES RF
84

REPORTED IES RG
95

REPORTED IES RCS,H1
-12

REPORTED DEFAULT LIGHT OUTPUT
11046 lm

Reported Electrical Performance 5 fields

REPORTED INPUT WATTAGE
78.9 W

REPORTED TOTAL HARMONIC DISTORTION
15 %

REPORTED POWER FACTOR
0.9

REPORTED DEFAULT INPUT WATTAGE
79.0 W

VOLTAGE RANGE

120-277 V

Tested Photometric Performance

No Applicable Data

Tested Electrical Performance

No Applicable Data

Indoor Amber

No Applicable Data

Field Adjustability

28 fields

FIELD ADJUSTABLE LIGHT OUTPUT (FALO)

Yes

FALO LIGHT OUTPUT AND WATTAGE SETTINGS

Light Output	7700 lm	10500 lm	11046 lm	N/A	N/A	N/A	N/A	N/A
Wattage	55 W	75 W	78.9 W	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE COLOR TEMPERATURE (FACT)

Yes

FACT SETTINGS

3500 K	3500 K	4000 K	5000 K	N/A	N/A	N/A	N/A	N/A

FIELD ADJUSTABLE LIGHT DISTRIBUTION (FALD)

No

Tunability

No Applicable Data

Solar

No Applicable Data

Sustainability

No Applicable Data

Product Images shown may not represent all capabilities or aesthetic options available for the associated model number